

# Gluing compound

For overlap joints of roofing felt

## General

Gluing Compound is strong binding asphalt cement that provides very durable and tight joints.

## Range of application

Gluing Compound is used to overlap joints of roofing felt on wooden roofs. It can also be used for sealing and repair jobs where flexible and elastic cement is required. It replaces for example heated asphalt for insulation purposes. Gluing Compound has strong gluing abilities which provide very durable and tight joints.

## Instructions for use

The consistence is influenced by the temperature and in cold weather we recommend heating in water-bath before using the product. The surface must be dry and clean. Apply Gluing Compound with a coarse spatula. If necessary, the product can be thinned with a little white spirit.

## Package

10800401 / 1-lit can (4 pieces per pack.)  
10800405 / 5-lit can

## Technical data

Density: 950 ± 20 kg/m<sup>3</sup>

Dry content: 76 ± 2 %

Solvent: White spirit

Drying time: Approx 1 week

Coverage: 1 liter/ 15 m overlap

Cleaning: White spirit

Drying time: Approx. 24 h (surface dry at +20°C)

**For further information we recommend the safety data sheet or instruction on package.**

Issue: 2023-11-01



Auson AB, Kungsbacka, Sweden  
T: +46 (0)300-56 20 00  
www.auson.se

These information are for guidance only and are given without obligation. If there is some confusion we recommend that you do your own tests and ask for advice in writing from us.